

Prize de cuplare KD4-1/4-I

Numar piesa: 531636

FESTO



 General operating condition

Fisa de date

| Caracteristica | Valoare |
|---|---|
| Latimea nominala | 7.2 mm |
| Presiune de functionare interval complet de temperatura | -0.095 MPa ... 1.2 MPa |
| Presiune de functionare interval complet de temperatura | -0.95 bar ... 12 bar |
| Presiune de functionare interval complet de temperatura | -13.775 psi ... 174 psi |
| Debit nominal standard (normalizat conform DIN 1343) | 257 l/min ... 1292 l/min |
| Debitul nominal standardizat conform ISO 8778 | 278.6 l/min ... 1400.5 l/min |
| Mediu de operare | Aer comprimat conform ISO 8573-1:2010 [7:-:-] |
| Nota referitoare la mediul de lucru/comanda | Este posibila functionarea cu ulei |
| Clasa de rezistenta la coroziune KBK | 1 - stres redus la coroziune |
| Conformitatea LABS | VDMA24364-B1/B2-L |
| Temperatura ambianta | -10 °C ... 60 °C |
| Cuplu de strangere nominal | 9.5 Nm |
| Toleranta fata de cuplul de strangere nominal | ± 15 % |
| Greutate produs | 88 g |
| Conector pneumatic 1 | Filet interior G1/4 |
| Nota privind materialele | Conform RoHS |
| Material garnituri | NBR |
| Material arc | otel inoxidabil aliaj inalt |
| Material carcasa | Alama, nichelata |
| Material piesa filetata | Alama, nichelata |
| Material inel interior | Alama |
| Material saiba elastica | Otel inoxidabil aliaj inalt |
| Material stifturi | Otel inalt aliat, inoxidabil |
| Material corp ventil | Alama |
| Manson de deblocare a materialului | PP |