

Pressing tool PZ 6/5

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



Crimping tools for wire end ferrules, with and without plastic collars

- Ratchet guarantees precise crimping
- Release option in the event of incorrect operation

General ordering data

Type	PZ 6/5
Order No.	9011460000
Version	Pressing tool, Crimping tool for wire-end ferrules, 0.25mm ² , 6mm ² , Trapezoidal indentation crimp
GTIN (EAN)	4008 190165352
Qty.	1 Stück

Pressing tool PZ 6/5

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technische Daten

Dimensions and weights

Width	200 mm	Width (inches)	7,874 inch
Weight	423 g	Net weight	433 g

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Technical data

Version	Mechanical, without interchangeable inserts
---------	---

Description of contact

Type of contact	Wire-end ferrules with/without plastic collars	Crimping range, min.	0,25 mm ²
Crimping range, max.	6 mm ²	Conductor cross-section, max. AWG	AWG 10
Conductor cross-section, min. AWG	AWG 24		

tool data crimping

Crimping profile 1, min.	0,25 mm ²	Crimping type/profile	Trapezoidal indentation crimp
Wire end ferrules cross-section, min.	0,25 mm ²	Crimping profile 1, max.	0,5 mm ²
Wire end ferrules cross-section, max.	6 mm ²	Crimping profile 2, min.	0,75 mm ²
Crimping profile 2, max.	1,5 mm ²	Crimping profile 3, min.	2,5 mm ²
Crimping profile 4, min.	4 mm ²	Crimping profile 5	6 mm ²

Classifications

ETIM 6.0	EC000168	ETIM 7.0	EC000168
eClass 9.0	21-04-38-11	eClass 9.1	21-04-38-11
eClass 10.0	21-04-38-11	UNSPSC	31-16-31-02

Approvals

Approvals



Downloads

Brochure/Catalogue	CAT 6 TOOLS 15/16 EN CAT 2 PORTFOLIOGUIDE EN
Engineering Data	WSCAD
User Documentation	Manual

Datenblatt

**Pressing tool
PZ 6/5**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Zeichnungen

