

Testing tools VT DIGI PRO

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com



The main function of the voltage tester is to establish if voltage is present. A 2-pole voltage tester is the only approved testing instrument that fulfils the requirements of work protection regulations.

- with LCD-Display
- acc. to VDE standard,
- high peak voltage strength
- the right tester for every application

General ordering data

| | |
|------------|---------------------------------|
| Type | VT DIGI PRO |
| Order No. | 9918870000 |
| Version | 2-pole voltage tester type 1152 |
| GTIN (EAN) | 4032248405756 |
| Qty. | 1 Stück |

Testing tools VT DIGI PRO

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technische Daten

Dimensions and weights

| | | | |
|--------|--------|-----------------|-------------|
| Width | 264 mm | Width (inches) | 10,394 inch |
| Height | 33 mm | Height (inches) | 1,299 inch |
| Depth | 67 mm | Depth (inches) | 2,638 inch |
| Weight | 295 g | Net weight | 444 g |

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

Measuring and testing devices

| | | | |
|---------------------------|---|----------------------------------|---|
| AC voltage display | 1 - 1,000 V | AC voltage measuring range | 1 - 1,000 V |
| Battery type | 1.5 V type AAA battery | Continuity test | Yes - visual + acoustic |
| DC voltage display | 1 - 1,000 V | DC voltage measuring range | 1000 V |
| Display | LCD digital | Frequency measurement | Yes |
| Frequency range, max. | 400 Hz | Frequency range, min. | 16 Hz |
| Input resistance, voltage | On operating the double switch $\geq 300 \text{ k}\Omega$ | Insulation test | 8 kV |
| Measuring range category | CAT III 1.000V / CAT IV 600V | Note | Screw-on, thicker test probes |
| Peak voltage resistance | 8 kV | Protection degree | IP65 |
| RCD circuit breaker | The selectable load enables conscious triggering of a 30 mA RCD circuit breaker | Rated voltage, max. | 1000 V AC/DC |
| Rated voltage, min. | 1 V | Tested and approved according to | IEC 61243-3:2014 (DIN EN 61243-3:2015-08) |
| Working temperature, max. | 55 °C | Working temperature, min. | -15 °C |

Classifications

| | | | |
|-------------|-------------|------------|-------------|
| ETIM 6.0 | EC000494 | ETIM 7.0 | EC000494 |
| eClass 9.0 | 27-20-03-08 | eClass 9.1 | 27-20-03-08 |
| eClass 10.0 | 27-20-03-08 | UNSPSC | 41-11-36-37 |

Approvals

Approvals



ROHS Conform

Downloads

| | |
|---|--|
| Approval/Certificate/Document of Conformity | 9918870000_DECLARATION_OF_CONFORMITY.pdf |
| Brochure/Catalogue | CAT 6 TOOLS 15/16 EN |
| Product Change Notification | PCN-PW641010-20180410-00-A DE PCN-PW641010-20180410-00-A EN |
| User Documentation | BANL_manual 2pol Tester |