

Contactor, 3 pole, 380 V 400 V 55 kW, RAC 24: 24 V 50/60 Hz, AC operation, Screw terminals



Part no. DILM115(RAC24)

239545

EL Number

4134054

(Norway)

General specifications		
Product name		Eaton Moeller® series DILM contactor
Part no.		DILM115(RAC24)
EAN		4015082395452
Product Length/Depth		160 millimetre
Product height		170 millimetre
Product width		90 millimetre
Product weight		2.25 kilogram
Certifications		CE UL UL 60947-4-1 UL File No.: E29096 CSA IEC/EN 60947-4-1 CSA File No.: 012528 UL Category Control No.: NLDX CSA-C22.2 No. 60947-4-1-14 CSA Class No.: 2411-03, 3211-04 VDE 0660 IEC/EN 60947
Product Tradename		DILM
Product Type		Contactor
Product Sub Type		None
Catalog Notes		Contacts according to EN 50012
Features & Functions		
Fitted with:		Suppressor circuit in actuating electronics
General information		
Application		Contactors for Motors
Degree of protection		IP00
Frame size		FS4
Lifespan, mechanical		10,000,000 Operations (AC operated)
Operating frequency		3600 mechanical Operations/h (AC operated)
Overvoltage category		III
Pollution degree		3
Product category		Contactors
Protection		Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)
Rated impulse withstand voltage (Uimp)		8000 V AC
Residual current		1 mA (with actuation of A1 - A2 by the electronics with "0" signal)
Resistance per pole		0.6 mΩ
Suitable for		Also motors with efficiency class IE3
Utilization category		AC-3: Normal AC induction motors: starting, switch off during running AC-1: Non-inductive or slightly inductive loads, resistance furnaces AC-4: Normal AC induction motors: starting, plugging, reversing, inching
Voltage type		AC
Ambient conditions, mechanical		
Shock resistance		10 g, N/O main contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms 10 g, N/O main contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms 5 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms 7 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms 7 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

		5 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms
Climatic environmental conditions		
Altitude		Max. 2000 m
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		60 °C
Ambient operating temperature (enclosed) - min		25 °C
Ambient operating temperature (enclosed) - max		40 °C
Ambient storage temperature - min		40 °C
Ambient storage temperature - max		80 °C
Climatic proofing		Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
Electro magnetic compatibility		
Emitted interference		According to EN 60947-1
Interference immunity		According to EN 60947-1
Terminal capacities		
Terminal capacity (copper band)		2 x (6 x 16 x 0.8) mm (Number of segments x width x thickness), Main cables
Terminal capacity (flexible with ferrule)		1 x (0.75 - 2.5) mm ² , Control circuit cables 1 x (10 - 95) mm ² , Main cables 2 x (0.75 - 2.5) mm ² , Control circuit cables 2 x (10 - 70) mm ² , Main cables
Terminal capacity (solid)		2 x (0.75 - 2.5) mm ² , Control circuit cables 1 x (0.75 - 4) mm ² , Control circuit cables
Terminal capacity (solid/stranded AWG)		Single 8...3/0, double 8...2/0, Main cables 18 - 14, Control circuit cables
Terminal capacity (stranded)		1 x (16 - 95) mm ² , Main cables 2 x (16 - 70) mm ² , Main cables
Stripping length (main cable)		24 mm
Stripping length (control circuit cable)		10 mm
Screw size		5 mm AF, Hexagon socket-head spanner, Terminal screw, Main cables M10, Terminal screw, Main cables M3.5, Terminal screw, Control circuit cables
Screwdriver size		2, Terminal screw, Control circuit cables, Pozidriv screwdriver 0.8 x 5.5/1 x 6 mm, Terminal screw, Control circuit cables, Standard screwdriver
Tightening torque		1.2 Nm, Screw terminals, Control circuit cables 14 Nm, Screw terminals, Main cables
Electrical rating		
Rated breaking capacity at 220/230 V		1150 A
Rated breaking capacity at 380/400 V		1150 A
Rated breaking capacity at 500 V		1150 A
Rated breaking capacity at 660/690 V		1100 A
Rated operational current (Ie) at AC-1, 380 V, 400 V, 415 V		160 A
Rated operational current (Ie) at AC-3, 220 V, 230 V, 240 V		115 A
Rated operational current (Ie) at AC-3, 380 V, 400 V, 415 V		115 A
Rated operational current (Ie) at AC-3, 440 V		115 A
Rated operational current (Ie) at AC-3, 500 V		115 A
Rated operational current (Ie) at AC-3, 660 V, 690 V		93 A
Rated operational current (Ie) at AC-4, 220 V, 230 V, 240 V		55 A
Rated operational current (Ie) at AC-4, 440 V		55 A
Rated operational current (Ie) at AC-4, 500 V		55 A
Rated operational current (Ie) at AC-4, 660 V, 690 V		45 A
Rated operational current (Ie) at DC-1, 60 V		160 A
Rated operational current (Ie) at DC-1, 110 V		160 A
Rated operational current (Ie) at DC-1, 220 V		90 A
Rated insulation voltage (Ui)		690 V
Rated making capacity up to 690 V (cos phi to IEC/EN 60947)		1610 A
Rated operational power at AC-3, 240 V, 50 Hz		40 kW
Rated operational power at AC-3, 380/400 V, 50 Hz		55 kW
Rated operational power at AC-3, 415 V, 50 Hz		70 kW
Rated operational power at AC-3, 440 V, 50 Hz		75 kW

Rated operational power at AC-3, 500 V, 50 Hz		85 kW
Rated operational power at AC-3, 690 V, 50 Hz		90 kW
Rated operational power at AC-4, 220/230 V, 50 Hz		17 kW
Rated operational power at AC-4, 240 V, 50 Hz		19 kW
Rated operational power at AC-4, 415 V, 50 Hz		33 kW
Rated operational power at AC-4, 440 V, 50 Hz		35 kW
Rated operational power at AC-4, 500 V, 50 Hz		40 kW
Rated operational power at AC-4, 660/690 V, 50 Hz		43 kW
Rated operational voltage (Ue) at AC - max		690 V
Short-circuit rating		
Short-circuit current rating (basic rating)		10 kA, SCCR (UL/CSA) 600 A, max. CB, SCCR (UL/CSA) 600 A, max. Fuse, SCCR (UL/CSA)
Short-circuit current rating (high fault at 480 V)		30/100 kA, Fuse, SCCR (UL/CSA) 300/300 A, Class J, max. Fuse, SCCR (UL/CSA) 65 kA, CB, SCCR (UL/CSA) 250 A, max. CB, SCCR (UL/CSA)
Short-circuit current rating (high fault at 600 V)		300/300 A, Class J, max. Fuse, SCCR (UL/CSA) 30 kA, CB, SCCR (UL/CSA) 350 A, max. CB, SCCR (UL/CSA) 30/100 kA, Fuse, SCCR (UL/CSA)
Short-circuit protection rating (type 1 coordination) at 400 V		250 A gG/gL
Short-circuit protection rating (type 1 coordination) at 690 V		250 A gG/gL
Short-circuit protection rating (type 2 coordination) at 400 V		250 A gG/gL
Short-circuit protection rating (type 2 coordination) at 690 V		250 A gG/gL
Conventional thermal current I_{th}		
Conventional thermal current I _{th} (1-pole, enclosed)		285 A
Conventional thermal current I _{th} (3-pole, enclosed)		115 A
Conventional thermal current I _{th} at 55°C (3-pole, open)		135 A
Conventional thermal current I _{th} at 60°C (3-pole, open)		130 A
Conventional thermal current I _{th} of main contacts (1-pole, open)		325 A
Switching capacity		
Switching capacity (main contacts, general use)		180 A, Maximum motor rating (UL/CSA)
Magnet system		
Arcing time		15 ms
Drop-out voltage		AC operated: 0.6 - 0.25 x UC, AC operated
Duty factor		100 %
Pick-up voltage		0.8 - 1.15 V AC x U _c
Power consumption, pick-up, 50 Hz		180 VA, Dual-frequency coil in a cold state and 1.0 x U _s , at 50 Hz
Power consumption, pick-up, 60 Hz		170 VA, Dual-frequency coil in a cold state and 1.0 x U _s , at 60 Hz
Power consumption, sealing, 50 Hz		2.3 W, Dual-frequency coil in a cold state and 1.0 x U _s , at 50 Hz 3.1 VA, Dual-frequency coil in a cold state and 1.0 x U _s , at 50 Hz
Power consumption, sealing, 60 Hz		2.3 W, Dual-frequency coil in a cold state and 1.0 x U _s , at 60 Hz 3.1 VA, Dual-frequency coil in a cold state and 1.0 x U _s , at 60 Hz
Rated control supply voltage (U _s) at AC, 50 Hz - min		24 V
Rated control supply voltage (U _s) at AC, 50 Hz - max		24 V
Rated control supply voltage (U _s) at AC, 60 Hz - min		24 V
Rated control supply voltage (U _s) at AC, 60 Hz - max		24 V
Rated control supply voltage (U _s) at DC - min		0 V
Rated control supply voltage (U _s) at DC - max		0 V
Switching time (AC operated, make contacts, closing delay) - min		28 ms
Switching time (AC operated, make contacts, closing delay) - max		33 ms
Switching time (AC operated, make contacts, opening delay) - min		35 ms
Switching time (AC operated, make contacts, opening delay) - max		41 ms
Motor rating		
Assigned motor power at 115/120 V, 60 Hz, 1-phase		10 HP
Assigned motor power at 200/208 V, 60 Hz, 3-phase		40 HP
Assigned motor power at 230/240 V, 60 Hz, 1-phase		25 HP
Assigned motor power at 230/240 V, 60 Hz, 3-phase		50 HP

Assigned motor power at 460/480 V, 60 Hz, 3-phase		100 HP
Assigned motor power at 575/600 V, 60 Hz, 3-phase		100 HP
Communication		
Connection		Screw terminals
Connection to SmartWire-DT		No
Contacts		
Number of auxiliary contacts (normally closed contacts)		0
Number of auxiliary contacts (normally open contacts)		0
Safety		
Safe isolation		690 V AC, Between the contacts, According to EN 61140 690 V AC, Between coil and contacts, According to EN 61140
Special purpose ratings		
Special purpose rating of ballast electrical discharge lamps		160 A (480V 60Hz 3phase, 277V 60Hz 1phase) 160 A (600V 60Hz 3phase, 347V 60Hz 1phase)
Special purpose rating of definite purpose rating		115 A, FLA 480 V 60 Hz 3-ph, 100,000 cycles acc. to UL 1995, (UL/CSA) 690 A, LRA 480 V 60 Hz 3-ph, 100,000 cycles acc. to UL 1995, (UL/CSA)
Special purpose rating of elevator control		30 HP, 200 V 60 Hz 3-ph, (UL/CSA) 40 HP, 240 V 60 Hz 3-ph, (UL/CSA) 75 HP, 480 V 60 Hz 3-ph, (UL/CSA) 104 A, 240 V 60 Hz 3-ph, (UL/CSA) 100 HP, 600 V 60 Hz 3-ph, (UL/CSA) 92 A, 200 V 60 Hz 3-ph, (UL/CSA) 96 A, 480 V 60 Hz 3-ph, (UL/CSA) 99 A, 600 V 60 Hz 3-ph, (UL/CSA)
Special purpose rating of refrigeration control (CSA only)		540 A, LRA 600 V 60 Hz 3phase; (CSA) 84 A, FLA 600 V 60 Hz 3phase; (CSA) 84 A, FLA 480 V 60 Hz 3phase; (CSA) 540 A, LRA 480 V 60 Hz 3phase; (CSA)
Special purpose rating of resistance air heating		160 A, 600 V 60 Hz 3phase, 347 V 60 Hz 1phase, (UL/CSA) 160 A, 480 V 60 Hz 3phase, 277 V 60 Hz 1phase, (UL/CSA)
Special purpose rating of tungsten incandescent lamps		160 A, 600 V 60 Hz 3phase, 347 V 60 Hz 1phase, (UL/CSA) 160 A, 480 V 60 Hz 3phase, 277 V 60 Hz 1phase, (UL/CSA)
Design verification		
Equipment heat dissipation, current-dependent Pvid		18.9 W
Heat dissipation capacity P _{diss}		0 W
Heat dissipation per pole, current-dependent Pvid		6.3 W
Rated operational current for specified heat dissipation (I _n)		115 A
Static heat dissipation, non-current-dependent P _{vs}		2.3 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Power contactor, AC switching (EC000066)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Power contactor, AC switching (ecl@ss10.0.1-27-37-10-03 [AAB718015])		
Rated control supply voltage U_s at AC 50HZ	V	24 - 24
Rated control supply voltage U_s at AC 60HZ	V	24 - 24
Rated control supply voltage U_s at DC	V	0 - 0
Voltage type for actuating		AC
Rated operation current I_e at AC-1, 400 V	A	160
Rated operation current I_e at AC-3, 400 V	A	115
Rated operation power at AC-3, 400 V	kW	55
Rated operation current I_e at AC-4, 400 V	A	55
Rated operation power at AC-4, 400 V	kW	28
Rated operation power NEMA	kW	74
Modular version		No
Number of auxiliary contacts as normally open contact		0
Number of auxiliary contacts as normally closed contact		0
Type of electrical connection of main circuit		Screw connection
Number of normally closed contacts as main contact		0
Number of normally open contacts as main contact		3