

Contactors, 3 pole, 380 V 400 V 75 kW, RAC 240: 190 - 240 V 50/60 Hz, AC operation, Screw terminals



**Part no. DILM150-EA(RAC240)
189927**

General specifications		
Product name		Eaton Moeller® series DILM contactor
Part no.		DILM150-EA(RAC240)
EAN		4015081879236
Product Length/Depth		160 millimetre
Product height		170 millimetre
Product width		90 millimetre
Product weight		2.25 kilogram
Compliances		RoHS conform CE CE Marked
Product Tradename		DILM
Product Type		Contactors
Product Sub Type		None
General information		
Voltage type		AC
Electrical rating		
Rated operational current (Ie) at AC-1, 380 V, 400 V, 415 V		190 A
Rated operational current (Ie) at AC-3, 380 V, 400 V, 415 V		150 A
Rated operational power at AC-3, 380/400 V, 50 Hz		75 kW
Magnet system		
Rated control supply voltage (Us) at AC, 50 Hz - min		190 V
Rated control supply voltage (Us) at AC, 50 Hz - max		240 V
Rated control supply voltage (Us) at AC, 60 Hz - min		190 V
Rated control supply voltage (Us) at AC, 60 Hz - max		240 V
Rated control supply voltage (Us) at DC - min		0 V
Rated control supply voltage (Us) at DC - max		0 V
Contacts		
Number of auxiliary contacts (normally closed contacts)		0
Number of auxiliary contacts (normally open contacts)		0

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Power contactor, AC switching (EC000066)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactors (LV) / Power contactor, AC switching (ecl@ss10.0.1-27-37-10-03 [AAB718015])			
Rated control supply voltage Us at AC 50HZ	V		190 - 240
Rated control supply voltage Us at AC 60HZ	V		190 - 240
Rated control supply voltage Us at DC	V		0 - 0
Voltage type for actuating			AC
Rated operation current Ie at AC-1, 400 V	A		190
Rated operation current Ie at AC-3, 400 V	A		150
Rated operation power at AC-3, 400 V	kW		75
Rated operation current Ie at AC-4, 400 V	A		75
Rated operation power at AC-4, 400 V	kW		33
Rated operation power NEMA	kW		93
Modular version			No
Number of auxiliary contacts as normally open contact			0
Number of auxiliary contacts as normally closed contact			0
Type of electrical connection of main circuit			Screw connection

Number of normally closed contacts as main contact		0
Number of normally open contacts as main contact		3