



**Control relays, Expandable, networkable (Ethernet), 12/24 V DC, 24 V AC, Digital: 8, of which can be used as analog: 4, Quantity of outputs: Relay: 4, screw terminal**



**Part no. EASY-E4-UC-12RC1**  
**Catalog No. 197211**

**EL-Nummer 4500546**  
**(Norway)**

**Delivery program**

Basic function			easyE4 base device
Description			Electronic control relay Rated operating voltage 12V DC, 24V DC or 24V AC 8 digital inputs with 12 VDC, 24 VDC or 24 VAC of these, 4 inputs can also be used as analog inputs and 4 inputs as fast counters 4 relay outputs for 12–250 VAC or 12–240 VDC with display Real-time clock with Ethernet interface Expandable with the easyE4 series of digital input/output expansions with easy-E4-CONNECT1 connector (Item Y7-197225) Expandable with communications modules EASY-COM-... Screw terminals
<b>Inputs</b>			
Digital			8
of which can be used as analog			4
<b>Outputs</b>			
Quantity of outputs			Relay: 4
<b>Additional features</b>			
Real time clock			#
Display & keypad			#
Expansions			Expandable networkable (Ethernet)
Supply voltage			12/24 V DC 24 V AC
Software			EASYSOFT-SWLIC/easySoft 7
Connection type			screw terminal

**Technical data**

<b>General</b>			
Standards			EN 61000-6-2 EN 61000-6-3 IEC 60068-2-6 IEC 60068-2-27 IEC 60068-2-30 IEC/EN 61131-2 EN 61010 EN 50178
Approvals			
Approvals certificate			cULus CE
shipping classification			DNV GL
Dimensions (W x H x D)		mm	71.5 x 90 x 58
Weight		kg	0.215
Mounting			Top-hat rail IEC/EN 60715, 35 mm or screw fixing using fixing brackets ZB4-101-GF1 (accessories)
Connection type			screw terminal
Ethernet			
Connections			RJ45 plug, 8-pin
Cable			CAT5

## Terminal capacities

Screw terminals			
Solid		mm <sup>2</sup>	0.2 - 4
flexible		mm <sup>2</sup>	0.2 - 2.5
Solid or flexible conductor, with ferrule		mm <sup>2</sup>	0,2 - 2,5
Solid or stranded		AWG	22 - 12
Standard screwdriver		mm	0.8 x 3.5
Tightening torque		Nm	0.5 - 0.7
Stripping length		mm	6.5

## Display

Display - Type			Monochrome
Lines x characters			6 x 16

## Climatic environmental conditions

Operating ambient temperature		°C	-25 to 55, cold as per IEC 60068-2-1, heat as per IEC 60068-2-2
Condensation			Take appropriate measures to prevent condensation
LCD display (clearly legible)		°C	0 - 55
Storage	θ	°C	-40 - +70
relative humidity		%	in accordance with IEC 60068-2-30, IEC 60068-2-78 5 - 95
Air pressure (operation)		hPa	795 - 1080

## Ambient conditions, mechanical

Protection type (IEC/EN 60529, EN50178, VBG 4)			IP20
Vibrations		Hz	In accordance with IEC 60068-2-6 constant amplitude 0.15 mm: 10 - 57 constant acceleration 2 g: 57 - 150
Mechanical shock resistance (IEC/EN 60068-2-27) semi-sinusoidal 15 g/11 ms		Impacts	18
Drop to IEC/EN 60068-2-31	Drop height	mm	50
Free fall, packaged (IEC/EN 60068-2-32)		m	0.3
Mounting position			Vertical or horizontal


## Electromagnetic compatibility (EMC)

Overvoltage category/pollution degree			III/2
Electrostatic discharge (ESD)			
applied standard			nach IEC/EN 61000-4-2
Air discharge		kV	8
Contact discharge		kV	6
Electromagnetic fields (RFI) to IEC EN 61000-4-3		V/m	0.08 - 1.0 GHz: 10 1.4 - 2 GHz: 3 2.0 - 2.7 GHz: 1
Radio interference suppression			EN 61000-6-3 Class B
Burst		kV	according to IEC/EN 61000-4-4 Supply cables: 2 Signal cables: 2
power pulses (Surge)			according to IEC/EN 61000-4-5 1 kV (supply cables, symmetrical) 2 kV (supply cables, asymmetrical)
Immunity to line-conducted interference to (IEC/EN 61000-4-6)		V	10

## Insulation resistance

Clearance in air and creepage distances			nach EN 50178, EN 61010-2-201, UL61010-2-201, CSA-C22.2 NO. 61010-2-201
Insulation resistance			per EN 50178, EN 61010-2-201, UL61010-2-201, CSA-C22.2 NO. 61010-2-201

## Back-up of real-time clock

Back-up of real-time clock			 <p>① Backup time (hours) with fully charged double layer capacitor ② Service life (years)</p>
Accuracy of the real-time clock		s/day	typ. ± 2 (± 0.2 h/Year)  depending on ambient air temperature fluctuations of up to ± 5 s/day (± 0.5 h/year) are possible

## Repetition accuracy of timing relays

Accuracy of timing relays (of values)		%	± 0.02
---------------------------------------	--	---	--------

Resolution			
Range "S"		ms	5
Range "M:S"		s	1
Range "H:M"		min	1

### Power supply

Rated operational voltage	U <sub>e</sub>	V	12/24 DC (-15/+20%) 24 AC (-15/+10%)
Permissible range	U <sub>e</sub>		10.2 - 28.8 V DC 20.4 - 26.4 V AC
Residual ripple		%	≤ 5
Protection against polarity reversal			yes
Frequency		Hz	50/60 (± 5%)
Input current			max. 200 mA at 12 V DC max. 125 mA at 24 V DC
Voltage dips		ms	≤ 20 ms at 24 V AC 10 ms at 24 V DC 1 ms at 12 V DC
Fuse		A	≥ 1A (T)
Power loss	P	W	Normally 3
Heat dissipation at 24 V DC		W	3

### Digital inputs 12 V DC

Number			8
Status Display			LCD-Display
Potential isolation			from power supply: no to the memory card: no to Ethernet: yes between inputs: no from the outputs: yes to expansion devices: yes
Rated operational voltage	U <sub>e</sub>	V DC	12
Input voltage		V DC	Condition 0: ≤ 5 (I1 - I8) Condition 1: ≥ 8 (I1 - I8)
Input current at signal 1		mA	1.75 mA (I1 - I4) 0.9 mA (I5 - I8)
Deceleration time		ms	20 (0 -> 1/1 -> 0, Debounce ON) type 0.015 (0 -> 1/1 -> 0, Debounce OFF)
Cable length		m	100 (unshielded)
Frequency counter			
Note			Notes on this, see under Digital inputs 24 V DC
Incremental counter			
Note			Notes on this, see under Digital inputs 24 V DC
Rapid counter inputs			
Note			Notes on this, see under Digital inputs 24 V DC

### Digital inputs 24 V DC

Number			8
Inputs can be used as analog inputs			4 (I5, I6, I7, I8)
Status Display			LCD-Display
Potential isolation			from power supply: no to the memory card: no to Ethernet: yes between inputs: no from the outputs: yes to expansion devices: yes
Rated operational voltage	U <sub>e</sub>	V DC	24
Input voltage		V DC	Signal 0: ≤ 5 (I1 - I8) Condition 1: ≥ 15 (I1 - I8)
Input current at signal 1		mA	3.3 (I1 - I4) 1.8 (I5 - I8)
Deceleration time		ms	20 (0 -> 1/1 -> 0, Debounce ON) type 0.015 (0 -> 1/1 -> 0, Debounce OFF)
Cable length		m	100 (unshielded)
Frequency counter			
Number			4 (I1, I2, I3, I4)
Counter frequency		kHz	≤ 5

Pulse shape			Square
Pulse pause ratio			1:1
Cable length		m	≤ 20 (screened)
<b>Incremental counter</b>			
Number of counter inputs			2 (I1 + I2, I3 + I4)
Value range			-2147483648 to +2147483647
Counter frequency		kHz	≤ 5
Pulse shape			Square
Signal offset			90°
Pulse pause ratio			1:1
Cable length		m	≤ 20 (screened)
<b>Rapid counter inputs</b>			
Number			4 (I1, I2, I3, I4)
Value range			-2147483648 to +2147483647
Counter frequency		kHz	≤ 10
Pulse shape			Square
Pulse pause ratio			1:1
Cable length		m	≤ 20 (screened)

### Digital inputs 24 V AC

Number			8
Status Display			LCD-Display
Potential isolation			from power supply: no to the memory card: no to Ethernet: yes between inputs: no from the outputs: yes to expansion devices: yes
Rated operational voltage	U <sub>e</sub>	V AC	24
Input voltage (AC = sinusoidal)	U <sub>e</sub>	V	Status 0: ≤ 5 (I1 - I8) Condition 1: ≥ 14 (I1 - I8)
Rated frequency		Hz	50/60
Input current at signal 1		mA	I1 - I4: 3.5 (at 24 VAC/DC) I5 - I8: 1.8 (at 24 VAC/DC)
Deceleration time		ms	45/38 (0 -> 1/1 -> 0, debounce ON 50/60Hz) type 25/21 (0 -> 1/1 -> 0, debounce OFF 50/60Hz)
Cable length		m	40 (unshielded)

### Analog inputs

Number			4 (I5, I6, I7, I8)
Potential isolation			from power supply: no to the memory card: no to Ethernet: yes between inputs: no from the outputs: yes to expansion devices: yes
Input type			DC voltage
Signal range			0-10 V DC
Resolution			12 Bit (value 0 - 4095)
Input impedance		kΩ	13.3
Accuracy of actual value			
two devices from series		%	± 3 , ± 0.12 V
Within a single device		%	± 2 , ± 0.12 V
Conversion time, analog/digital		ms	each CPU cycle
Input current		mA	< 1
Cable length		m	≤ 30, screened

### Relay outputs

Number			4
Outputs in groups of			1
Parallel switching of outputs for increased output			Not allowed
Protection of an output relay			Miniature circuit-breaker B16 or slow-blow 8 A fuse
Potential isolation			Safe isolation according to EN 50178: 300 V AC Basic isolation: 600 V AC from power supply: yes From the inputs: yes

			between outputs: yes to Ethernet: yes to expansion devices: yes
<b>Contacts</b>			
Conventional thermal current (10 A UL)		A	8
Recommended for load: 12 V AC/DC		mA	> 500
Rated impulse withstand voltage $U_{imp}$ of contact coil		kV	6
Rated operational voltage	$U_e$	V AC	240
Rated insulation voltage	$U_i$	V AC	240
Safe isolation according to EN 50178		V AC	300 between coil and contact 300 between two contacts
<b>Making capacity</b>			
AC—15, 250 V AC, 3 A (600 ops./h)	Operations		300000
DC-13, L/R $\leq$ 150 ms, 24 V DC, 1 A (500 S/h)	Operations		200000
<b>Breaking capacity</b>			
AC-15, 250 V AC, 3 A (600 Ops./h)	Operations		300000
DC-13, L/R $\leq$ 150 ms, 24 V DC, 1 A (500 S/h)	Operations		200000
<b>Filament bulb load</b>			
1000 W at 230/240 V AC	Operations		25000
500 W at 115/120 V AC	Operations		25000
<b>Fluorescent lamp load</b>			
Fluorescent lamp load 10 x 58 W at 230/240 V AC			
With upstream electrical device	Operations		25000
Uncompensated	Operations		25000
Fluorescent lamp load 1 x 58 W at 230/240 V AC, conventional, compensated	Operations		25000
<b>Switching frequency</b>			
Mechanical operations		$\times 10^6$	10
Switching frequency		Hz	10
Resistive load/lamp load		Hz	2
Inductive load		Hz	0.5
<b>UL/CSA</b>			
Uninterrupted current at 240 V AC		A	10
Uninterrupted current at 24 V DC		A	8
<b>AC</b>			
Control Circuit Rating Codes (utilization category)			B 300 Light Pilot Duty
Max. rated operational voltage		V AC	300
max. thermal continuous current $\cos \varphi = 1$ at B 300		A	5
max. make/break $\cos \varphi \neq 1$ capacity 1 at B 300		VA	3600/360
<b>DC</b>			
Control Circuit Rating Codes (utilization category)			R 300 Light Pilot Duty
Max. rated operational voltage		V DC	300
Max. thermal uninterrupted current at R 300		A	1
Max. make/break capacity at R 300		VA	28/28
<b>Ethernet</b>			
Data transfer rate		Mbit/s	10/100
Connections			RJ45 plug, 8-pin
Cable			CAT5

## Design verification as per IEC/EN 61439

<b>Technical data for design verification</b>			
Static heat dissipation, non-current-dependent	$P_{Vs}$	W	3
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	55
<b>IEC/EN 61439 design verification</b>			
10.2 Strength of materials and parts			
10.2.2 Corrosion resistance			Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of ASSEMBLIES		Meets the product standard's requirements.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9 Insulation properties		
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 8.0



Programmable logic controllers PLC (EG000024) / Logic module (EC001417)		
Electric engineering, automation, process control engineering / Control / Programmable logic control (SPS) / Logic module (ecl@ss10.0.1-27-24-22-16 [AKE539014])		
Supply voltage AC 50 Hz	V	85 - 264
Supply voltage AC 60 Hz	V	85 - 264
Supply voltage DC	V	10.2 - 28.8
Voltage type of supply voltage		AC/DC
Switching current	A	8
Number of analogue inputs		0
Number of analogue outputs		0
Number of digital inputs		8
Number of digital outputs		4
With relay output		Yes
Number of HW-interfaces industrial Ethernet		1
Number of interfaces PROFINET		0
Number of HW-interfaces RS-232		0
Number of HW-interfaces RS-422		0
Number of HW-interfaces RS-485		0
Number of HW-interfaces serial TTY		0
Number of HW-interfaces USB		0
Number of HW-interfaces parallel		0
Number of HW-interfaces Wireless		0
Number of HW-interfaces other		0
With optical interface		No
Supporting protocol for TCP/IP		Yes
Supporting protocol for PROFIBUS		No
Supporting protocol for CAN		No
Supporting protocol for INTERBUS		No
Supporting protocol for ASI		No
Supporting protocol for KNX		No
Supporting protocol for Modbus		Yes

Supporting protocol for Data-Highway			No
Supporting protocol for DeviceNet			No
Supporting protocol for SUCONET			No
Supporting protocol for LON			No
Supporting protocol for PROFINET IO			No
Supporting protocol for PROFINET CBA			No
Supporting protocol for SERCOS			No
Supporting protocol for Foundation Fieldbus			No
Supporting protocol for EtherNet/IP			No
Supporting protocol for AS-Interface Safety at Work			No
Supporting protocol for DeviceNet Safety			No
Supporting protocol for INTERBUS-Safety			No
Supporting protocol for PROFIsafe			No
Supporting protocol for SafetyBUS p			No
Supporting protocol for other bus systems			No
Radio standard Bluetooth			No
Radio standard Wi-Fi 802.11			No
Radio standard GPRS			No
Radio standard GSM			No
Radio standard UMTS			No
IO link master			No
Redundancy			No
With display			Yes
Degree of protection (IP)			IP20
Basic device			Yes
Expandable			Yes
Expansion device			No
With time switch clock			Yes
Rail mounting possible			Yes
Wall mounting/direct mounting			Yes
Front built-in possible			Yes
Rack-assembly possible			No
Suitable for safety functions			No
SIL according to IEC 61508			None
Performance level according to EN ISO 13849-1			None
Appendant operation agent (Ex ia)			No
Appendant operation agent (Ex ib)			No
Explosion safety category for gas			None
Explosion safety category for dust			None
Width		mm	72
Height		mm	90
Depth		mm	58

## Approvals

UL File No.			E205091
UL Category Control No.			NRAQ/7
North America Certification			UL listed
Degree of Protection			IEC: IP20, UL/CSA Type: -

## Dimensions





## Additional product information (links)

### assembly instructions easyE4 IL050020ZU

assembly instructions easyE4 IL050020ZU	<a href="https://es-assets.eaton.com/DOCUMENTATION/AWA_INSTRUCTIONS/IL050020ZU.pdf">https://es-assets.eaton.com/DOCUMENTATION/AWA_INSTRUCTIONS/IL050020ZU.pdf</a>
---	---

### easyE4 (MN050009) manual

easyE4 – Handbuch (MN050009) - Deutsch	<a href="https://es-assets.eaton.com/DOCUMENTATION/AWB_MANUALS/MN050009_DE.pdf">https://es-assets.eaton.com/DOCUMENTATION/AWB_MANUALS/MN050009_DE.pdf</a>
--	---

easyE4 (MN050009) manual - English	<a href="https://es-assets.eaton.com/DOCUMENTATION/AWB_MANUALS/MN050009_EN.pdf">https://es-assets.eaton.com/DOCUMENTATION/AWB_MANUALS/MN050009_EN.pdf</a>
------------------------------------	---

manuel easyE4 (MN050009) - français	<a href="https://es-assets.eaton.com/DOCUMENTATION/AWB_MANUALS/MN050009_FR.pdf">https://es-assets.eaton.com/DOCUMENTATION/AWB_MANUALS/MN050009_FR.pdf</a>
-------------------------------------	---

Manuale easy E4 (MN050009) - italiano	<a href="https://es-assets.eaton.com/DOCUMENTATION/AWB_MANUALS/MN050009_IT.pdf">https://es-assets.eaton.com/DOCUMENTATION/AWB_MANUALS/MN050009_IT.pdf</a>
---------------------------------------	---

instrukcja easyE4 (MN050009) - polski	<a href="https://es-assets.eaton.com/DOCUMENTATION/AWB_MANUALS/MN050009_PL.pdf">https://es-assets.eaton.com/DOCUMENTATION/AWB_MANUALS/MN050009_PL.pdf</a>
---------------------------------------	---

f1=1454&f2=1174&f3=1755;Download Software easySoft V7	<a href="http://applications.eaton.eu/sdlc?LX=11&amp;f1=1454&amp;f2=1174&amp;f3=1755;Download Software easySoft V7">http://applications.eaton.eu/sdlc?LX=11&amp;f1=1454&amp;f2=1174&amp;f3=1755;Download Software easySoft V7</a>
---	---

Product overview (WEB)	<a href="http://www.eaton.eu/easyE4">http://www.eaton.eu/easyE4</a>
------------------------	---