

Thermistor overload relay for machine protection, 1N/O+1N/C, 24-240VAC/DC, with reclosing lockout



Part no. EMT6-KDB
269471
EL Number 4110424
(Norway)

General specifications	
Product name	Eaton Moeller® series EMT6 Thermistor overload relay
Part no.	EMT6-KDB
EAN	4015082694715
Product Length/Depth	103 millimetre
Product height	83 millimetre
Product width	23 millimetre
Product weight	0.132 kilogram
Certifications	CSA IEC/EN 61000-4-2 CSA File No.: 12528 CSA-C22.2 No. 14 IEC/EN 60947-8 IEC/EN 60947 CE UL File No.: E29184 CSA Class No.: 3211-03 UL Category Control No.: NKCR VDE 0660 UL UL 508 EN 55011 IEC/EN 61000-4-3
Product Tradename	EMT6
Product Type	Thermistor overload relay
Product Sub Type	None
Features & Functions	
Electric connection type	Screw connection
Functions	Manual reset Notifications of mains and faults via LED display Short-circuit in the sensor cable Test function via separate button External reset possible Manual or remote resetting
Temperature measuring range - min	0 °C
Temperature measuring range - max	0 °C
General information	
Degree of protection	IP20
Mounting position	As required
Overvoltage category	III
Pollution degree	3
Product category	EMT6 thermistor overload relay for machine protection
Protection	Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)
Rated impulse withstand voltage (Uimp)	6000 V AC 4000 V AC
Safe isolation	250 V AC, Between the contacts, According to EN 61140 250 V AC, Between the contacts and power supply, According to EN 61140
Shock resistance	10 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms
Voltage type	AC/DC
Climatic environmental conditions	
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	60 °C
Ambient operating temperature (enclosed) - min	25 °C
Ambient operating temperature (enclosed) - max	45 °C
Ambient storage temperature - min	45 °C

Ambient storage temperature - max		85 °C
Climatic proofing		Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
Electro magnetic compatibility		
Air discharge		8 kV
Burst impulse		1 kV, Signal cable 2 kV, Supply cable According to IEC/EN 61000-4-4
Contact discharge		6 kV, Electrostatic discharge (ESD)
Electromagnetic fields		3 V/m at 1.4 - 2 GHz (according to IEC EN 61000-4-3) 1 V/m at 2.0 - 2.7 GHz (according to IEC EN 61000-4-3) 10 V/m at 80 - 1000 MHz (according to IEC EN 61000-4-3)
Immunity to line-conducted interference		10 V (according to IEC/EN 61000-4-6)
Radio interference class		Class B (EN 55011)
Surge rating		2 kV, symmetrical, power pulses (Surge), EMC According to IEC/EN 61000-4-5, power pulses (Surge), EMC 4 kV, asymmetrical, power pulses (Surge), EMC
Terminal capacities		
Terminal capacity		1 x (0.5 - 2.5) mm ² , flexible with ferrule 1 x (0.5 - 2.5) mm ² , solid 2 x (0.5 - 1.5) mm ² , flexible with ferrule 20 - 14 AWG, solid or stranded 2 x (0.5 - 1.5) mm ² , solid
Screw size		M3.5, Terminal screw
Screwdriver size		2, Terminal screw, Pozidriv screwdriver 1 x 6 mm, Terminal screw, Standard screwdriver
Tightening torque		1.2 Nm, Screw terminals
Electrical rating		
Conventional thermal current I _{th} of auxiliary contacts (1-pole, open)		6 A
Pick-up voltage		0.85 - 1.1 V x U _#
Power consumption		2 W at DC 3.5 VA at AC
Rated control supply voltage (U _s) at AC, 50 Hz - min		24 V
Rated control supply voltage (U _s) at AC, 50 Hz - max		240 V
Rated control supply voltage (U _s) at AC, 60 Hz - min		24 V
Rated control supply voltage (U _s) at AC, 60 Hz - max		240 V
Rated control supply voltage (U _s) at DC - min		24 V
Rated control supply voltage (U _s) at DC - max		240 V
Rated insulation voltage (U _i)		400 V
Rated operational current (I _e)		3 A at AC-14, 380 V 400 V 415 V (NC) 1 A at AC-15, 300 V (NC) 3 A at AC-14, 400 V (NC) 3 A at AC-14, 300 V (NO) 1 A at AC-15, 300 V (NO) 1 A at AC-15, 380 V 400 V 415 V (NO) 3 A at AC-15, 220 V 230 V 240 V 3 A at AC-14, 300 V (NC) 3 A at AC-14, 380 V 400 V 415 V (NO) 3 A at AC-15, 220 V 230 V 240 V (NO) 1 A at AC-15, 380 V 400 V 415 V (NC) 3 A at AC-15, 220 V 230 V 240 V (NC)
Rated operational voltage (U _e) - max		240 V
Reset resistance		1600 Ω
Short-circuit protection rating		Max. 6 A gG/gL, Fuse, Contacts
Trip resistance		3600 Ω
Voltage rating - max		600 V
Contacts		
Number of contacts (change-over contacts)		0
Number of contacts (normally closed contacts)		1
Number of contacts (normally open contacts)		1
Design verification		
Equipment heat dissipation, current-dependent P _{vid}		0 W
Heat dissipation capacity P _{diss}		0 W
Heat dissipation per pole, current-dependent P _{vid}		0 W

Rated operational current for specified heat dissipation (In)		0 A
Static heat dissipation, non-current-dependent Pvs		0.8 W

Technical data ETIM 8.0

Relays (EG000019) / Temperature monitoring relay (EC001446)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Monitoring equipment (low-voltage switch technology) / Temperature monitoring equipment (ecl@ss10.0.1-27-37-18-10 [AKF104014])

Type of electric connection		Screw connection
Rated control supply voltage Us at AC 50HZ	V	24 - 240
Rated control supply voltage Us at AC 60HZ	V	24 - 240
Rated control supply voltage Us at DC	V	24 - 240
Voltage type for actuating		AC/DC
With detachable clamps		No
Number of measuring circuits		1
Error registration possible		No
External reset possible		Yes
Number of contacts as normally closed contact		1
Number of contacts as normally open contact		1
Number of contacts as change-over contact		0
Temperature measuring range	°C	0 - 0
Resistance measuring range	Ohm	750 - 12000
Width	mm	23
Height	mm	83
Depth	mm	103