

Position switch, 1N/O+1N/C, basic, magnet-powered interlock



Part no. LS-S11-230AMT-ZBZ/X
106828
EL Number 4356180
(Norway)

General specifications	
Product name	Eaton Moeller® series LS Position switch
Part no.	LS-S11-230AMT-ZBZ/X
EAN	4015081065882
Product Length/Depth	55 millimetre
Product height	170 millimetre
Product width	37 millimetre
Product weight	0.417 kilogram
Certifications	UL File No.: E29184 IEC/EN 60947-5 UL CE IEC/EN 60947 UL 508 CSA Class No.: 3211-03 CSA File No.: 012528 CSA CSA-C22.2 No. 14 UL Category Control No.: NKCR
Product Tradename	LS
Product Type	Position switch
Product Sub Type	None
Catalog Notes	Contacts with safety function, by positive opening to IEC/EN 60947-5-1 For degree of protection IP65, use V-M20 (206910) cable glands with connecting thread of max. 9 mm length. Monitoring of door position: continuous The operating head can be rotated manually in 90° steps without tools to suit the specified level of actuation. Time control of the release operation possible using ESR5-NV3-30 With the actuator inserted, the N/O contact is open and the N/C contact is closed.
Features & Functions	
Electric connection type	Cable entry metrical
Enclosure material	Insulated material Plastic
Features	Forced opening Expandable
Fitted with:	Interlock monitoring
Switch function type	Slow-action switch
General information	
Connection type	Screw terminal
Degree of protection	IP65 NEMA Other
Duty factor	100 % (Magnet)
Lifespan	1,000,000 mechanical Operations
Operating frequency	800 Operations/h
Overvoltage category	III
Pollution degree	3
Product category	Basic units with spring-powered interlock (closed-circuit principle)
Rated impulse withstand voltage (Uimp)	4000 V AC
Repetition accuracy	0.02 mm (Contacts/switching capacity)
Suitable for	Safety functions
Ambient conditions, mechanical	
Mounting position	As required
Shock resistance	10 g, Standard-action contact, Mechanical, Half-Sinusoidal shock 20 ms
Climatic environmental conditions	

Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		70 °C
Climatic proofing		Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
Terminal capacities		
Terminal capacity (flexible with ferrule)		1 x (0.5 - 1.5) mm ² 2 x (0.5 - 1.5) mm ²
Terminal capacity (solid)		2 x (0.75 - 1.5) mm ² 1 x (0.75 - 2.5) mm ²
Electrical rating		
Power consumption		8 W at 24 V DC (electromechanical actuation) 8 VA at 120 V AC (electromechanical actuation) 11 VA at 230 V AC (electromechanical actuation)
Rated conditional short-circuit current (I _q)		1 kA
Rated control supply voltage		230 V 50/60 Hz (Us, for magnet drive)
Rated insulation voltage (Ui)		400 V
Rated operational current (I _e) at AC-15, 220 V, 230 V, 240 V		6 A
Rated operational current (I _e) at AC-15, 24 V		6 A
Rated operational current (I _e) at AC-15, 380 V, 400 V, 415 V		4 A
Rated operational current (I _e) at DC-13, 110 V		0.8 A
Rated operational current (I _e) at DC-13, 125 V		0.8 A
Rated operational current (I _e) at DC-13, 220 V, 230 V		0.3 A
Rated operational current (I _e) at DC-13, 24 V		3 A
Short-circuit protection rating		Max. 6 A gG/gL, Fuse, Contacts
Supply frequency		Max. 400 Hz, Contacts
Actuator		
Actuating force at beginning/end of stroke		25 N/15 N (plug-in/pull-out)
Actuator type		None
Mechanical holding force		1600 N (according to GS-ET-19 (04/2004), XWA, XFG, XF) 1700 N (according to GS-ET-19 (04/2004), XG, XW, XNG) 1200 N (according to GS-ET-19 (04/2004), XNW)
Contacts		
Number of contacts (change-over contacts)		0
Number of contacts (normally closed contacts)		1
Number of contacts (normally open contacts)		1
Safety		
Explosion safety category for gas		None
Explosion safety category for dust		None
Design verification		
Equipment heat dissipation, current-dependent P _{vid}		0 W
Heat dissipation capacity P _{diss}		0 W
Heat dissipation per pole, current-dependent P _{vid}		0.13 W
Rated operational current for specified heat dissipation (I _n)		6 A
Static heat dissipation, non-current-dependent P _{vs}		0 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 8.0

Sensors (EG000026) / End switch (EC000030)

Electric engineering, automation, process control engineering / Binary sensor technology, safety-related sensor technology / Safety-related position switch / Safety position switch (Type 1)
(ec1@ss10.0.1-27-27-26-01 [AKE640013])

Width sensor	mm	60
Diameter sensor	mm	0
Height of sensor	mm	173
Length of sensor	mm	39
Rated operation current I _e at AC-15, 24 V	A	6
Rated operation current I _e at AC-15, 125 V	A	6
Rated operation current I _e at AC-15, 230 V	A	6
Rated operation current I _e at DC-13, 24 V	A	3
Rated operation current I _e at DC-13, 125 V	A	0.8
Rated operation current I _e at DC-13, 230 V	A	0.3
Switching function		Slow-action switch
Switching function latching		No
Output electronic		No
Forced opening		Yes
Number of safety auxiliary contacts		1
Number of contacts as normally closed contact		1
Number of contacts as normally open contact		1
Number of contacts as change-over contact		0
Type of interface		None
Type of interface for safety communication		None
Construction type housing		Cuboid
Material housing		Plastic
Coating housing		Other
Type of control element		None
Alignment of the control element		Other
Type of electric connection		Cable entry metrical
With status indication		No
Suitable for safety functions		Yes
Explosion safety category for gas		None
Explosion safety category for dust		None
Ambient temperature during operating	°C	-25 - 70
Degree of protection (IP)		IP65
Degree of protection (NEMA)		Other