Neutral conductor, switched neutral, for P3

Powering Business Worldwide*

Part no. N-P3E 062432

EL Number 1456528

(Norway)

(Norway)	
General specifications	
Product name	Eaton Moeller® series Accessory Neutral conductor
Part no.	N-P3E
EAN	4015080624325
Product Length/Depth	50 millimetre
Product height	50 millimetre
Product width	50 millimetre
Product weight	0.07 kilogram
Certifications	UL 508 CSA-C22.2 No. 94 UL UL Category Control No.: NLRV IEC/EN 60947-3 CSA CSA Class No.: 3211-05 UL File No.: E36332 CSA File No.: 012528 CE CSA-C22.2 No. 14-05
Product Tradename	None
Product Type	Accessory
Product Sub Type	Neutral conductor
Catalog Notes	N-P1(P3) switching capacity same as for contacts P1(P3) The N contact always behaves as an early-make contact when switching on and as a late-break contact when switching off.
General information	
Accessory/spare part type	Neutral terminal
Mounting position	Left side Right side
Туре	Neutral conductor Switchable neutral conductor
Climatic environmental conditions	
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	50 °C
Terminal capacities	
Stripping length (main cable)	13.5 mm
Electrical rating	
Rated operational current (le) - max	90 A
Design verification	
Equipment heat dissipation, current-dependent Pvid	0 W
	0 VV
Heat dissipation capacity Pdiss	
Heat dissipation per pole, current-dependent Pvid	7.5 W
Rated operational current for specified heat dissipation (In)	100 A
Static heat dissipation, non-current-dependent Pvs	0 W
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Meets the product standard's requirements.
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions	Meets the product standard's requirements.
10.3 Degree of protection of assemblies	Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances	Meets the product standard's requirements.
10.5 Protection against electric shock	Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components	Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections	Is the panel builder's responsibility.
10.8 Connections for external conductors	Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength	Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage	Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material	Is the panel builder's responsibility.
10.10 Temperature rise	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Accessories/spare parts for low-voltage switch technology (EC002498)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Component for low-voltage switch technology (accessories) (ecl@ss10.0.1-27-37-13-92 [AKN570013])

Type of accessory/spare part	Neutral terminal
Accessory	Yes
Spare part	No