

## Ba15d continuous light module; green

**Part no.** SL7-L-G  
**171434**  
**EL Number** 4137689  
**(Norway)**

General specifications		
Product name		Eaton Moeller® series SL7 Continuous light module
Part no.		SL7-L-G
EAN		4015081677665
Product Length/Depth		73 millimetre
Product height		73 millimetre
Product width		73 millimetre
Product weight		0.075 kilogram
Certifications		Certified by UL for use in Canada CSA-C22.2 No. 14-10 UL Category Control No.: NKCR CSA Class No.: NKCR7 UL report applies to both US and Canada UL File No.: E29184 IEC/EN 60529 IEC/EN 60947-5-1 UL 508 CE CSA-C22.2 No. 94-91 UL
Product Tradename		SL7
Product Type		Continuous light module
Product Sub Type		None
Catalog Notes		Without light elements
Features & Functions		
Color		Green
Enclosure color		Black
Functions		Continuous light
Light modules		Filament lamp max. 7 W
Number of modules		Max. 10 (with base for mounting on both sides) Max. 5 (with standard base)
General information		
Connection to SmartWire-DT		No
Degree of protection		NEMA 13 IP66
Lifespan, electrical		3,000 h
Light type		Continuous light
Material		Cap: Polycarbonate (PC) Enclosure: Polycarbonate (PC)
Mounting Method		BA15d lamp socket
Mounting position		As required
Overvoltage category		III
Pollution degree		3
Product Category		SL signal towers
Radiation angle		360 °
Rated impulse withstand voltage (Uimp)		4000 V AC
Shock resistance		Mechanical, According to IEC/EN 60068-2-27 15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms
Type		Continuous light module
Voltage type		AC/DC
Climatic environmental conditions		
Ambient operating temperature - min		-30 °C
Ambient operating temperature - max		60 °C
Climatic proofing		Damp heat, constant, to IEC 60068-2-78

			Damp heat, cyclic, to IEC 60068-2-30
<b>Electrical rating</b>			
Leakage current			0.003 A
Power consumption			Max. 7 W with the specified voltages
Rated insulation voltage (Ui)			250 V
Rated operational voltage (Ue) at AC - min			24 V
Rated operational voltage (Ue) at AC - max			250 V
Rated operational voltage (Ue) at DC - min			24 V
Rated operational voltage (Ue) at DC - max			250 V

## Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Optical module for signal tower (EC000232)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Optical module for signal tower (ecl@ss10.0.1-27-37-12-20 [AKF038014])			
Function			Continuous light
Colour			Green
Outer diameter		mm	73
Operating voltage at AC 50 Hz		V	24 - 250
Operating voltage at AC 60 Hz		V	24 - 250
Operating voltage at DC		V	24 - 250
Voltage type			AC/DC
Lamp type			None
Colour housing			Black
Degree of protection (IP)			IP66
Degree of protection (NEMA)			13